

# Best Available Copy

## AMENDMENTS TO THE CLAIMS

Kindly amend claims 2, 3, 6, 10, 12, and 17. Please cancel claims 1, 4-5, 7-9, 13-16, and 18-21. Claims pending in the application become:

1. (Canceled):

2. (Currently Amended): ~~The A supersonic aircraft according to Claim 1~~  
~~wherein comprising:~~  
a fuselage extending forward and aft along a longitudinal axis, the fuselage having a  
lower surface and an upper surface;  
a highly swept low aspect ratio wing coupled to the fuselage, the wing having a  
forward leading edge and an aft trailing edge;  
an effector flap coupled to the wing trailing edge;  
a tail empennage coupled to the fuselage aft of the wing on the fuselage upper surface  
in a position high relative to the wing, the tail empennage forming a channel  
region subject to complex shock patterns the tail empennage has and having an  
inverted V-tail geometry coupled to the wing in a braced wing configuration  
further comprising a vertical stabilizer, lateral inverted stabilizers, and inverted  
V-tail control surface ruddervators; and  
an effector coupled to the tail empennage; and  
a controller coupled to the effector flaps and the effectors, the controller further  
comprising a control process that reduces drag through channel relief by  
deflecting both the effector flap down and the effector up, and the controller  
~~further comprises~~ a control process capable of adjusting the aircraft  
longitudinal lift distribution for a selected supersonic Mach number to  
maintain a low sonic-boom, low drag-trim condition.

KOESTNER BERTANI LLP  
18663 MACARTHUR BLVD.  
SUITE 400  
IRVINE, CA 92612  
TEL (949) 231-0200  
FAX (949) 231-0260

3. (Currently Amended): The A supersonic aircraft according to Claim 1 wherein comprising:

a fuselage extending forward and aft along a longitudinal axis, the fuselage having a lower surface and an upper surface;

a highly swept low aspect ratio wing coupled to the fuselage, the wing having a forward leading edge and an aft trailing edge;

an effector flap coupled to the wing trailing edge;

a tail empennage coupled to the fuselage aft of the wing on the fuselage upper surface in a position high relative to the wing, the tail empennage forming a channel region subject to complex shock patterns, and having the tail empennage has a supersonic T-tail geometry further comprising a vertical stabilizer, a lateral horizontal stabilizer, and a control surface elevator; and

an effector coupled to the tail empennage; and

a controller coupled to the effector flaps and the effectors, the controller further comprising a control process that reduces drag through channel relief by deflecting both the effector flap down and the effector up, and the controller further comprises a control process capable of adjusting the aircraft longitudinal lift distribution for a selected supersonic Mach number to maintain a low sonic-boom, low drag-trim condition.

4. (Canceled):

5. (Canceled)

Best Available Copy

6. (Currently Amended): The A supersonic aircraft according to Claim 1 further comprising:

a fuselage extending forward and aft along a longitudinal axis, the fuselage having a lower surface and an upper surface;

a highly swept low aspect ratio wing coupled to the fuselage, the wing having a forward leading edge and an aft trailing edge;

an effector flap coupled to the wing trailing edge;

engines coupled to the aft portion of the wing lower surface; and

KOESTNER BERTANI LLP  
18003 MACARTHUR BLVD.  
SUITE 400  
IRVINE, CA 92613  
TEL (949) 251-0250  
FAX (949) 251-0260

a tail empennage coupled to the fuselage aft of the wing on the fuselage upper surface in a position high relative to the wing, the tail empennage forming a channel region subject to complex shock patterns and an inverted V-tail geometry empennage coupled to the wing in a braced wing configuration and carrying lift at the aft portion of the aircraft on a high mounted tail, the length of the aircraft being effectively lengthened for shock waves below the aircraft, thereby further reducing sonic boom, the inverted V-tail carrying tail lift high to maintain a continuous lift distribution and structurally bracing the wing and engines;

an effector coupled to the tail empennage; and

a controller coupled to the effector flaps and the effectors, the controller further comprising a control process that reduces drag through channel relief by deflecting both the effector flap down and the effector up.

7. (Canceled):

8. (Canceled):

9. (Canceled):

10. (Currently Amended): ~~The~~ A supersonic aircraft according to Claim 7 further comprising:

an aircraft body extending forward and aft;

a highly swept low aspect ratio wing coupled to the body, the wing having a forward leading edge and an aft trailing edge;

an effector flap coupled to the trailing edge of the wing;

an inverted V-tail coupled at the aft portion of the aircraft body and coupled to the wing in a braced wing configuration, the inverted V-tail forming a channel region that can generate complex shock patterns;

two wing-mounted engines positioned beneath the wing at an aft location, the braced wing V-tail supporting the engines and enabling trim for a low sonic boom lift distribution;

KOESTNER BERTANI LLP  
13603 MACARTHUR BLVD  
SUITE 400  
IRVINE, CA 92618  
TEL. (949) 251-0250  
FAX (949) 251-0260

ruddervator control surfaces coupled to the inverted V-tail; and  
a controller coupled to the effector flap and the ruddervator control surfaces, the  
controller comprising a control process that reduces drag through channel  
relief by deflecting both the effector flap down and the ruddervator control  
surfaces up.

11. (Original): The aircraft according to Claim 10 wherein:  
the engines have a highly integrated wing/inlet geometry that enables low-boom  
compatibility and low inlet/nacelle installation drag.

12. (Currently Amended): ~~The A supersonic aircraft according to Claim 7~~  
~~wherein comprising:~~

an aircraft body extending forward and aft;  
a highly swept low aspect ratio wing coupled to the body, the wing having a forward  
leading edge and an aft trailing edge;  
an effector flap coupled to the trailing edge of the wing;  
an inverted V-tail coupled at the aft portion of the aircraft body and coupled to the  
wing in a braced wing configuration, the inverted V-tail forming a channel  
region that can generate complex shock patterns;  
ruddervator control surfaces coupled to the inverted V-tail; and  
a controller coupled to the effector flap and the ruddervator control surfaces, the  
controller comprising a control process that reduces drag through channel  
relief by deflecting both the effector flap down and the ruddervator control  
surfaces up, and the controller further comprises a control process that adjusts  
aircraft longitudinal lift distribution for a selected Mach number to maintain a  
low sonic boom, low drag-trim condition..

13. (Canceled):

14. (Canceled):

15. (Canceled):

KOESTNER BERTANI LLP  
18003 MACARTHUR BLVD  
SUITE 400  
IRVING, CA 92612  
TEL (949) 331-4230  
FAX (949) 331-4260

16. (Canceled):

17. (Currently Amended): The A channel control system according to Claim 15 for usage in a supersonic aircraft including a fuselage, wings, a tail empennage, and a plurality of control effectors coupled to the wings and the tail empennage, the empennage and wings forming a channel region that can form complex shock patterns at transonic speeds, the channel control system comprising:

a plurality of actuators coupled to the control effectors, the effectors including a flap coupled to the wing and an effector coupled to the tail empennage; and  
at least one vehicle management computer coupled to the plurality of actuators, the at least one vehicle management computer further comprising a process for  
managing the control effectors in a drag reduction mode through channel relief  
by deflecting both the flap downward and the tail empennage effector upward,  
wherein:

the wing is a highly swept low aspect ratio wing coupled to the body, the wing having a forward leading edge and an aft trailing edge, and an effector flap coupled to the trailing edge of the wing;

the tail empennage is in a configuration of an inverted V-tail coupled at the aft portion of the aircraft body and coupled to the wing in a braced wing configuration, the tail empennage comprising ruddervator control surfaces coupled to the inverted V-tail; and

the at least one vehicle management computer further comprises a channel relief process that reduces drag through channel relief by deflecting both the effector flap downward and the ruddervator upward.

18. (Canceled):

19. (Canceled):

20. (Canceled):

KOESTNER BERTANI LLP  
18662 MACARTHUR BLVD.  
SUITE 400  
IRVINE, CA 92612  
TEL (949) 251-0250  
FAX (949) 251-0360

21. (Canceled):

KOESTNER BERTANI LLP  
18561 MACARTHUR BLVD.  
SUITE 400  
IRVING, CA 92612  
TEL (949) 231-0250  
FAX (949) 231-0260